

MICREWUBE® WITH LIP SEAL SCREW CAP

T336

WITH LIP SEAL SCREW CAP AND ATTACHMENT LOOP

Made of polyethylene and polypropylene



The flexible sealing lip inside the cap ensures a positive leakproof seal under even the most adverse conditions. This deep internal lip fits snugly against the interior wall of the tube preventing the contents from coming in contact with the threads, thus reducing the chances of sample contamination. This series of tubes is available either plain or with printed graduations and white marking area for sample identification.

Caps are supplied with attachment loops in order to prevent contamination and mix-up. These microcentrifuge tubes have all the other fine features stated in the general description, but cannot be autoclaved since closure is made of high density polyethylene. Non skirted tubes can be centrifuged up to 17,000g.

Will withstand temperatures from -90 °C to +100 °C.



T338

WITH LIP SEAL SCREW CAP

Made of polyethylene and polypropylene



Similar to the T336 Series but without the “tethered cap” feature.

This series of tubes is available either plain or with printed graduations and white marking area for sample identification. They have all the other fine features of the T336 series of tubes, but the caps are not supplied with the attachment loop for users who prefer to remove the caps completely from the tubes when filling or sampling. Cannot be autoclaved since closure is made of high density polyethylene. Non skirted tubes can be centrifuged up to 17,000g.

Will withstand temperatures from -90 °C to +100 °C.



T339

WITH LIP SEAL AND FLAT SCREW CAP

Made of polyethylene and polypropylene



This series of tubes is available either plain or with printed graduations and white marking area for sample identification. Lip seal screw caps are unattached but incorporate a flat top which provides a writing surface. These flat surfaced tubes can also be used with automatic capping machines and in packaging industries. Closures are supplied in natural color. Tubes are made of polypropylene while polyethylene caps are easy to screw on and off. More economical than T335 Series O-ring seal model. Cannot be autoclaved since closure is made of high density polyethylene. Non skirted tubes can be centrifuged up to 17,000g.

Will withstand temperatures from -90 °C to +100 °C.

